

DEXTER HYSOL AEROSPACE INC DIV OF EXTER CORP -- EPK 0150 PART B -- 6080-01-358-9686

=====
Product Identification
=====

Product ID:EPK 0150 PART B
MSDS Date:05/20/1988
FSC:6080
NIIN:01-358-9686
Status Code:A
Kit Part:Y
MSDS Number: CJGPB
=== Responsible Party ===
Company Name:DEXTER HYSOL AEROSPACE INC DIV OF EXTER CORP
Address:2850 WILLOW PASS ROAD
Box:312
City:PITTSBURG
State:CA
ZIP:94565-3237

Country:US
Info Phone Num:510-458-8000
Emergency Phone Num:415-687-4201
CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address:2850 WILLOW PASS ROAD
Box:312
City:BAY POINT
State:CA
ZIP:94565-3299

Country:US
Phone:202-483-7616
CAGE:33564
Company Name:LUCENT TECHNOLOGIES
Address:2000 NE EXPY
Box:UNKNOW
City:NORCROSS
State:GA
ZIP:30071

Country:US
Phone:770-798-3846
CAGE:1K705

=====
Composition/Information on Ingredients
=====

===

Ingred Name:SILICA
CAS:7631-86-9
< Wt:5.
OSHA PEL:20 MPPCF

Ingred Name:TRIETHYLENETETRAMINE
CAS:112-24-3
RTECS #:YE6650000
< Wt:30.

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MATERIAL IS CORROSIVE TO SKIN. MAY
CAUSE CHEMICAL BURN TO EYES AND SKIN. REPEAT CONTACT M
AY CAUSE
SENSITIZATION.
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER
Effects of Overexposure:POSSIBLE BURNS TO EYES AND SKIN, IRRITATION AND
POSSIBLE SENSITIZATION TO SKIN.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER

===== First Aid Measures =====

First Aid:FLUSH SKIN AND EYES WITH PLENTY OF WATER. WASH SKIN
THOROUGHLY WITH SOAP 7 WATER, RUBBING ALCOHOL OR HAND CLEANER. DO
NOT USE SOLVENTS. REMOVE SOI
LED CLOTHES AND WASH BEFORE REUSE. IF
IRRITATION PERSI STS, SEE PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:=129.4C, 265.F
Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER
SPRAY, FOAM, FOG
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN
FIGHTING FIRES IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE
LIBERATED.

===== A

ccidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHES, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT ROOM TEMPERATURE (70 DE G F) FOR 12 MONTHS.

Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER

Supplemental Safety and Health

NONE SPEC

IFIED BY MANUFACTURER. KEY1=B2.

===== Physical/Chemical Properties =====

HCC:B2

Boiling Pt:=277.2C, 531.F

Vapor Pres:1

Spec Gravity:0.98

Evaporation Rate & Reference: