

ALLIED ENTERPRISES, INC. -- TASK FORCE -- 6850-01-376-1201

===== Product Identification =====

Product ID:TASK FORCE

MSDS Date:01/01/2000

FSC:6850

NIIN:01-376-1201

Status Code:A

MSDS Number: CKJGT

=== Responsible Party ===

Company Name:ALLIED ENTERPRISES, INC.

Address:814 W. 45TH STREET

Box:6159

City:NORFOLK

State:VA

ZIP:23508-2008

Country:US

Info Phone Num:757-489-8282

Emergency Phone Num:800-5

35-5063

CAGE:58396

=== Contractor Identification ===

Company Name:ALLIED ENTERPRISES, INC.

Address:814 W. 45TH STREET

Box:6159

City:NORFOLK

State:VA

ZIP:23508-2008

Country:US

Phone:757-489-8282

Contract Num:SP0450-00-M-D940

CAGE:58396

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: TO 100%

Ingred Name:TRIPROPYLENEGLYCOL METHYL ETHER OR GLYCOL ETHER

CAS:25498-49-1

RTECS #:UB8070000

Minumum % Wt:0.

Maxumum %

Wt:5.

Ingred Name:POTASSIUM HYDROXIDE

CAS:1310-58-3

RTECS #:TT2100000

Minumum % Wt:0.

Maxumum % Wt:5.

ACGIH STEL:C2 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NP (NONIONIC SURFACTANT)

CAS:9016-45-9

RTECS #:AX0247000

Minumum % Wt:0.

Maxumum % Wt:5.

Ingred Name:SODIUM METASILICATE

CAS:6834-92-0

RTECS #:VV9275000

Minumum % Wt:0.

Maxumum % Wt:5.

Ingred Name:TETRASODIUM EDTA

CAS:64-02-8

RTECS #:AH5075000

Minumum % Wt:0.

Maxumum % Wt:5.

Ingred Name:DYE

Minumum % Wt:0.

Maxumum % W

t:5.

===== Hazards Identification =====

LD50 LC50 Mixture:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Health Hazards Acute and Chronic:SKIN: SKIN IRRITANT. MAY CAUSE

MODERATE REDDENING AND SWELLING. EYES: EYE IRRITANT. LIQUID AND MISTS MAY DAMAGE EYES CAUSING CORNEAL DAMAGE. INHALATION: VAPORS AND MISTS MAY BE IRRITATING TO MUCOUS MEMBRANES IN THE NOSE, THROAT, AND LUNGS. INGESTION: IRRITATING AND CORROSIVE TO THE MOUTH AND THROAT. MAY CAUSE HE

ADACHE, NAUSEA, ABDOMINAL PAIN, VOMITING AND DIARRHEA. EXCESSIVE AMOUNTS MAY CAUSE COLL APSE.
Explanation of Carcinogenicity:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Effects of Overexposure:SKIN: SKIN IRRITANT. MAY CAUSE MODERATE REDDENING AND SWELLING. EYES: EYE IRRITANT. LIQUID AND MISTS MAY DAMAGE EYES CAUSING CORNEAL DAMAGE. INHALATION: VAPORS AND MISTS MAY BE IRRITATING TO MUCOUS ME MBRANES IN THE NOSE, THROAT, AND LUNGS. INGESTION: IRRITATING AND CORROSIVE TO THE MOUTH AND THROAT.
MAY CAUSE HEADACHE, NAUSEA, ABDOMINAL PAIN, VOMITING AND DIARRHEA. EXCESSIVE AMOUNTS MAY CAUSE COLL APSE.
Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY RESPONSIBLE PARTY.

=====
===== First Aid Measures =====

First Aid:SKIN: FLUSH WITH WATER. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: FLUSH WITH LARGE QUANTITIES OF WATER, HOLDING EYELIDS OPEN. SEEK MEDICAL ATTENTION, IF IRRITATION PERSISTS. INHALATION: GET FRESH AIR. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INGESTION: DO NOT INDUCE VOMITING. DRINK LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Fire Fighting Procedures:NON FLAMMABLE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:MOP UP OR OTHERWISE ABSORB AND HOLD FOR DISPOSAL.
Neutralizing Agent:NO DATA PROVIDED BY RESPONSIBLE PARTY.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. KEEP OUT OF REACH OF CHILDREN. FOR USE BY TRAINED PERSONNEL ONLY.
Other Precautions:KEEP CONTAINER CLOSED DURING STORAGE. DRINK LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IMMEDIATELY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE IN WELL VENTILATED AREA.
Ventilation:PROVIDE LOCAL EXHAUST TO KEEP

TLV BELOW ACCEPTABLE LIMIT.

Protective Gloves:CHEMICAL RESISTANT RUBBER OR NEOPRENE.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:EYEWASH STATION, CHEMICAL RESISTANT APRON.

Work Hygienic Practices:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Supplemental Safety and Health

NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:=98.9C, 210.F

Vapor Pres:20MMHG@68F

Vapor Density:>1

Spec Gravity:1.032

pH:13.0-13.5

Evapor

ation Rate & Reference: