

DEFT INC -- CAT, 1-COAT, TT-P-2756,30219 -- 8010-01-376-3708

===== Product Identification =====

Product ID:CAT, 1-COAT, TT-P-2756,30219

MSDS Date:02/28/1994

FSC:8010

NIIN:01-376-3708

Status Code:A

MSDS Number: CKKWH

=== Responsible Party ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Info Phone Num:949-474-0400

Emergency Phone Num:800-424-9300

P

reparer's Name:JULIETTE LIM

Chemtrec Ind/Phone:(800)424-9300

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE

CAS:123-86-4

RTECS #:AF7350000

= Wt:15.

OSHA PEL:150 PPM

OSHA STEL:200 PPM

ACGIH TLV:150 PPM

ACGIH STEL:200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:

ETHYL 3-ETHOXYPROPANOATE

CAS:763-69-9

RTECS #:UF3325000

= Wt:20.

Ingred Name:ALIPHATIC ISOCYANATE

= Wt:60.

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE: VAPORS ARE IRRITATING TO EYES, NOSE, AND THROAT. INHALATION MAY CAUSE HEADACHES, DIFFICULT BREATHING AND LOSS OF CONSCIOUSNESS. CHRONIC: PROLONGED CONTACT WILL CAUSE DRYING AND CRACKING OF THE SKIN, DUE TO DEFATTING ACTION. SKIN SENSITIZATION, ASTHMA OR OTHER ALLERGIC RESPONSES MAY DEVELOP.

Effects of Overexposure:INHALATION: IRRITATION OF THE RESPIRATORY TRACT AND ACUTE NERVOUS SYSTEM DEPRESSTION CHARACTERIZED BY THE FOLLOWING PROGRESSIVE STEPS: HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNES S OR COMA. SKIN AND EYE CONTACT: CONTACT WITH THE SKIN CAN CAUSE IRRITATION. SYMPTOMS MAY BE SWELLING, REDNESS, AND RASH. EYES: LIQUID, AREOSOLS, OR VAPORS ARE IRRITATING AND MAY CAUSE TEARING, R EDNESS, AND S

WELLING

ACCOMPANIED BY A STINGING SENSATION. SKIN ABSORPTION: PROLONGED OR REPEATED CONTACT CAN CAUSE MODEATE IRRITATION, DRYING, AND DEFATTING OF THE SKIN WHICH CAN CAUSE THE SKIN TO C RACK. *

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMITITIS.

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE TO AN AREA FREE FROM RISK OF FUTHER EXPOSURE. RESTORE BREATHING . ASTHMATIC TYPE SYMPTOMS MAY DEVELOP AND MAY BE IMMEDIATE OR DELAYED BY SEVERAL HOURS. OBTAIN MEDICAL ATTENTION. S KIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. WASH CONTAMINATED CLOTHING THOROUGHLY BEFORE REUSE. EYES: FLUSH WITH CLEAN LUKEWARM WATER (LOW PRESSURE) F OR AT LEAST 15 MINUTES, OCCASIONALLY LIFTING EYELIDS. OBTAIN MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIO

US PERSON. OBTAIN
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=7.8C, 46.F

TCC 46F

Lower Limits:1.000%

Upper Limits:13.10%

Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG,
WATER SPRAY

Fire Fighting Procedures:FULL FIRE FIGHTING EQUIPMENT WITH
SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING
SHOULD BE WORN BY FIRE FIGHTERS. WATER MAY BE USED TO COOL CLOSED
CONT

AINERS TO PREVENT PRESSURE BUILD -UP, AUTO IGNITION OR
EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CNTAINRS TIGHTLY CLSED. ISLTE FROM
HEAT, SPRKS, ELCTRCL EQPMNT &OPEN FLAME. CLSED CNTAINRS MAY EXPLDE
WHEN EXPSD TO EXTRME HEAT. APPLCATION TO HOT SRFCE S RQUIRES
SPCIAL PRCAUTIONS. DURING EM RGNCY CNDITIONS OVERXPOSURE TO
DECMPSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE
IMMEDIATELY APPARENT.

===== Accidental Release Measures =====

=====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE
ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES).
VENTILATE AREA CONTAIN AND REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY
WITH OSHA 1910.106 AVOID STORING NEAR HIGH TEMPERATURES, FIRE, OPEN
FLAMES, AND SPARK SOURCES. STORE IN TIGHTLY CL
OSED CONTAINERS.

STORE IN WELL VENTILATED ARE AS.

Other Precautions:KEEP CONTAINERS TIGHT AND UPRIGHT TO PREVENT LEAKAGE.
PREVENT PROLONGED BREATHING OF VAPORS OR SPRAY MISTS. PROLONGED
OVEREXPOSURE MAY CAUSE AND ALLERGIC REACTION. AVOD CONTACT WITH
SKIN AND EYES. DO NOT TAKE INTERNALLY. DO NOT HANDLE UNTIL THE
MANUFACTURERS SAFETY PRECAUTIONS HAVE BEEN READ AN D UNDERSTOOD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A

RESPIRATOR THAT IS RECOMMENDED OR APPROVED FOR USE IN AN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING OR FRESH AIR SUPPLIED) IS NECESSARY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE. VENTILATION SHOULD BE PROVIDED TO KEEP EXPOSURE LEVELS BELOW THE OSHA PERMISSIBLE LIMITS. **

Ventilation:EXHAUST VENTILATION SUFFICIENT TO KEEP THE AIRBORNE CONCENTRATIONS OF SOLVENT VAPORS OR MISTS BELOW THEIR RESPECTIVE TLV'S MUST BE UTILIZED.

Protective Gloves:PROTECTIVE GLOVES ARE RECOMMENDED (COTTON, NEOPRENE, RUBBER POLYTHYLENE)

Eye Protection:GOGGLES FACE SHIELD, SPLASH GUARD OR SIDE SHEILDS.

Other Protective Equipment:THE USE OF LONG SLEEVE AND LONG LEG CLOTHING IS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

**IF TLV LIMITS CAN BE MAINTAINED AND DOCUMENTED BELOW THE OSHA/ACGIH LIMITS, AN AIR SUPPLIED RESPIRATOR MAY NOT BE REQUIRED. HOWEVER, OTHER OSHA/NIOSH APPROVED RESPIRATORS MAY BE USED. REMOVE ALL

IG

NITION SOURCES (HEAT, SPARKS, FLAME, AND HOT SURFACES).

===== Physical/Chemical Properties =====

Boiling Pt:>126.7C, 260.F

B.P. Text:260-460F

Vapor Density:HEAVIER

Spec Gravity:1.03121

VOC Pounds/Gallon:400

Viscosity:THIN-THICK

Evaporation Rate & Reference:0.47 X BUTYL ACETATE

Solubility in Water:INSOLLUBLE

Appearance and Odor:AMBER LIQUID W/SOLVENT ODOR

Percent Volatiles by Volume:41.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIXING AGENTS.

Stability Condition to Avoid:HIGH TEMPERAUTRES, SPARKS, OR OPEN FLAMES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN.

===== Toxicological Information =====

Toxicological Information:*INGESTION: ACUTE: CAN RESULT IN IRRITATION

AND POSSIBLE CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE AND DIGESTIVE TRACT. VOMITIN

G MAY CAUSE ASPIRATION OF THE SOLVENT,
RESULTING IN CHEMICAL PNEUMONITIS. THIS PRODUCT CONTAINS THE
FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF
SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW
ACT OF 1986 AND OF 40 CFR 372: XYLENE, YELLOW TITANATE PIGMENT
AND ETHYL BENZENE.

===== Disposal Considerations =====

Waste Disposal Methods: WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL
LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY
CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE AND
FLAMMABLE VAPOR DO NOT INCINERATE CLOSED CONTAINERS.

===== MSDS Transport Information =====

Transport Information: APPLICABLE REGULATIONS: 49 CFR YES PROPER
SHIPPING NAME: PAINT UN: 1263 HAZARD CLASS: FLAMMABLE LIQUID 3
REQUIRED LABELS: FLAMMABLE LIQUID U.S. POSTAL REGULATION: NOT
ALLOWED TO SEND VIA US POSTAL SERVICE.

===== Regulatory Information =====

SARA Title III Information: THIS PRODUCT CONTAINS THE FOLLOWING TOXIC
CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF
THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND
40 CFR 372: 1330-20-7 XYLENE, 100-41-4 ETHYL BENZENE

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies)

:

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.