

DISTEC INC -- TFL 50(R) WET LUBE -- 8030-01-333-6230

===== Product Identification =====

Product ID:TFL 50(R) WET LUBE

MSDS Date:06/19/1997

FSC:8030

NIIN:01-333-6230

Status Code:A

MSDS Number: CKMCR

=== Responsible Party ===

Company Name:DISTEC INC

Address:914 ARTIC STREET BLDG #777

City:BRIDGEPORT

State:CT

ZIP:06608

Country:US

Info Phone Num:203-334-0383

Emergency Phone Num:(800)424-9300

Chemtec

Ind/Phone:(800)424-9300

CAGE:0TGR5

=== Contractor Identification ===

Company Name:DISTEC INC

Address:914 ARTIC STREET BLDG #777

Box:City:BRIDGEPORT

State:CT

ZIP:06608

Country:US

Phone:203-334-0383 / 800-643-6735

CAGE:0TGR5

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

&lt; Wt:35.

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE

CAS:9031-72-5

&lt; Wt:55.

Ingred Name:CARBON DIOXIDE

CAS:124-38-9  
RTECS #:FF6400000  
&lt; Wt:25.  
OSHA PEL:5000 PPM  
ACGIH TLV:5000 PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:INHALATION: MAY CAUSE IRRITATION OF  
RESPIRATORY TRACT, NAUSEA, DIZZINESS, HEADACHE AND DEPRESSION OF THE  
CENTRAL NERVOUS SYSTEM. INTENTIONAL MISUSE BY DELIBERATELY  
CONCENTRATING AND INHALING CAN BE HAR MFUL OR FATAL. INGESTION: MAY  
CAUSE GASTRO  
INTESTINAL IRRITATION, NAUSEA, VOMITING AND DEPRESSION  
OF THE CENTRAL NERVOUS SYSTEM. SKIN: MAY CAUSE IRRITATION. EYE: MAY  
CAUSE IRRITATION. MAY CAUSE CONJUNC TIVITIS OF THE EYES.  
Effects of Overexposure:MAY CAUSE SKIN IRRITATION ON PROLONGED OR  
REPEATED CONTACT.  
Medical Cond Aggravated by Exposure:NONE RECOGNIZED

=====  
First Aid Measures  
=====

First Aid:INHALATION: IF USER EXPERIENCES BREATHING DIFFCULTY, MOVE TO  
AIR FREE OF VAPORS. ADMINI  
STER OXYGEN OR ARTIFICIAL RESPIRATION  
UNTIL MEDICAL ASSISTANCE CAN BE RENDERED. INGESTION: DO NOT INDUCE  
VOMITING . CALL POISON CONTROL CENTER, HOSPITAL, EMERGENCY ROOM OR  
PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. EYE: FLUSH  
WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINITUES. IF  
IRRITATION FROM C ONTACT PERSISTS, GET MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Extinguishing Media:USW CARBON SIOXIDE, DRY POWDER OR  
FOAM  
Fire Fighting Procedures:SELF-CONTAINED RESPRITORY PROTECTION SHOULD BE  
PROVIDED FOR FIREFIGHTERS FIGHTING FLAMES IN BUILDINGS OR CONFINES  
AREAS. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH  
WATER SPRAY TO PREV ENT PRESSURE BUILD-UP.  
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. DO NOT PUNCTURE,  
INCINERATE OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED  
EXPOSURE TO SUN MAY CAUSE BURSTING. ISOLATE FROM HEAT, ELECTRICAL  
EQUIPMENT, SPARKS, OPE

N FLAMES ANS HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS. VENTILATE AREA. FLUSH  
LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS  
WITH LARGE QUANTITIES OF WATER. SMALL SPILLS CAN BE ABSORBED BY  
INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR FLAMES OR AT  
ELEVATED TEMPATURES.

Other Precau

tions:READ CAREFULLY ALL CAUTIONS ON PRODUCT LABEL BEFORE  
USE. SINCE EMPTY CONTAINER RETAINS RESIDUE, FOLLOW ALL WARNING EVEN  
AFTER CONTAINER IS EMOTY. DISPOSE OF EMPTY CONTAINER ACCORDING TO  
LOCAL REGULATI ONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OSHA CONTROLLED WORKPLACE, USE ONLY WITH  
ADEQUATE VENTILATION UNDER ENGINEERD AIR CONTROL SYSTEMS DESIGNED  
TO PROVIDE MAXIMUM APPROPRIATE TLV. FOR OCCASIONAL USE WHERE  
ENGI

NEERED AIR CONTROL IS NOT FEA SIABLE, USE NIOSH APPROVED  
RESPIRATORS. FOR OCCASIONAL CONSUMER USE, USE ONLY WITH ASEQUATE  
VENTILATION.

Ventilation:ADEQUATE VENTILATION MUST BE PROVIDED.

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:SAFTEY GLASSES, CHEMICAL GOGGLES OR FACE SHIELDS.

Work Hygienic Practices:WASH HANDS THROUGHLY AFTER USE. BEFORE REUSE,  
THROUGHLY CLEAN ANY CLOTHING OR PROTECTIVE EQUIPMENT WICH HAS BEEN  
CONTAMINATED BY PRIOR USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:644F,340C

Vapor Pres: