

EXIDE CORP -- STORAGE BATTERY -- 6140-01-210-1963

===== Product Identification =====

Product ID:STORAGE BATTERY

MSDS Date:04/01/1996

FSC:6140

NIIN:01-210-1963

Status Code:A

MSDS Number: CKRVN

=== Responsible Party ===

Company Name:EXIDE CORP

Address:645 PENN STREET

Box:14205

City:READING

State:PA

ZIP:19612-4205

Country:US

Info Phone Num:610-378-0500/0798

Emergency Phone Num:610-378-0500

CAGE:20

038

=== Contractor Identification ===

Company Name:EXIDE CORP

Address:645 PENN STREET

Box:14205

City:READING

State:PA

ZIP:19612-4205

Country:US

Phone:610-378-0500/0798

CAGE:20038

===== Composition/Information on Ingredients =====

Ingred Name:SULFURIC ACID

CAS:7664-93-9

RTECS #:WS5600000

Minumum % Wt:30.

Maxumum % Wt:40.

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3

ACGIH STEL:3 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Minumum % W

t:60.  
Maxumum % Wt:70.

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:THIS MSDS IS BASED ON THE  
MANUFACTURER'S MSDS FOR THE BATTERIES ELECTROLYTE, SULFURIC ACID.  
ACUTE: BURNS, SEVERE IRRITATION OF SKIN, EYES, MOUTH, THROAT,  
ESOPHAGUS, AND STOMACH; INFLAMMATION OF BRONCHIAL MEMBRANES.  
CHRONIC: EROSION OF TEETH; INFLAMMATION OF NOSE, THROAT, AND  
BRONCHIAL TUBES.

Ex  
planation of Carcinogenicity:IARC HAS CLASSIFIED "STRONG INORGANIC  
ACID MIST CONTAINING SULFURIC ACID" AS CATEGORY 1 CARCINOGEN, A  
SUBSTANCE CARCINOGENIC TO HUMANS. THIS CLASSIFICATION DOES NOT  
APPLY TO LIQUID FORMS OF SULFURIC ACID OR SULFURIC ACID SOLUTIONS  
CONTAINED IN A LEAD-ACID BATTERY. INORGANIC ACID MIST (SULFURIC  
ACID MIST) IS NOT GENERATED DURING NORMAL USE OF THIS PRODUCT.  
Effects of Overexposure:COUGH, INCREASED RESPIRATORY RATE; STINGING;  
BURNING SENSATION O  
N SKIN, EYE IRRITATION; DISCOLORATION OF TEETH.  
Medical Cond Aggravated by Exposure:EXPOSURE TO MIST MAY CAUSE LUNG  
DAMAGE AND AGGRAVATE PULMONARY CONDITIONS.

=====  
First Aid Measures  
=====

First Aid:REMOVE FROM EXPOSURE. FLUSH SKIN AND EYES FOR 15 MINUTES WITH  
LARGE AMOUNTS OF COOL WATER. IF INGESTED, DO NOT INDUCE VOMITING.  
CONSULT PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point:NOT COMBUSTIBLE  
Ex  
tinguishing Media:DRY CHEMICAL; CARBON DIOXIDE; WATER FOG; WATER.  
Fire Fighting Procedures:WATER APPLIED TO SULFURIC ACID GENERATES HEAT  
AND CAUSES ACID TO SPATTER. WEAR FULL-COVER SULFURIC ACID RESISTANT  
CLOTHING.  
Unusual Fire/Explosion Hazard:REACTS VIOLENTLY WITH METALS, NITRATES,  
CHLORATES, CARBIDES AND OTHER ORGANIC MATERIAL. REACTS WITH MOST  
METALS TO YIELD EXPLOSIVE/FLAMMABLE HYDROGEN GAS.

=====  
Accidental Release Measures  
=====

Spill Release

Procedures:STOP FLOW OF MATERIAL. FOR SMALL SPILLS,  
NEUTRALIZE WITH SODA ASH, LIME, OR SODIUM BICARBONATE. DILUTE  
CAUTIOUSLY WITH WATER. WEAR ACID-RESISTANT PROTECTIVE CLOTHING AND  
EQUIPMENT.

Neutralizing Agent:SODA ASH, LIME, SODIUM BICARBONATE. DILUTE  
CAUTIOUSLY WITH WATER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORAGE/HANDLING AREAS SHOULD BE  
EQUIPPED WITH EYEWASHES AND SAFETY SHOWERS. HANDLE CAUTIOUSLY;

AVOID CONTACT WITH SKIN AND EYES.

Other Precautions:HANDLING/STORAGE AREAS SHOULD BE EQUIPPED WITH PROPER  
CONTAINMENT TO CAPTURE AND NEUTRALIZE SPILLS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF CONCENTRATIONS EXCEED  
PEL, USE NIOSH-APPROVED FULL FACE RESPIRATOR.

Ventilation:LOCAL EXHAUST FOR 150 PPM EXPOSURE. MECHANICAL (GENERAL)  
WITH CAPACITY OF 3-4 AIR CHANGES PER HOUR. USE ACID-RESISTANT  
VENTILATION C

OMPONENTS.

Protective Gloves:RUBBER/PLASTIC WITH ELBOW LENGTH GAUNTLET.

Eye Protection:CHEMICAL GOGGLES; SAFETY GLASSES/FACE SHIELD.

Other Protective Equipment:ACID-RESISTANT APRON, BOOTS.

Work Hygienic Practices:HANDLE CAUTIOUSLY; AVOID CONTACT WITH SKIN AND  
EYES.

Supplemental Safety and Health

THIS MSDS IS BASED ON THE MANUFACTURER'S MSDS FOR THE BATTERY'S  
ELECTROLYTE, SULFURIC ACID.

=====  
===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:=95.C, 203.F

B

.P. Text:@ 14.7 PSIA.

Vapor Pres:10 MM HG @18F

Vapor Density:>1

Spec Gravity:1.245 TO 1.295

Evaporation Rate & Reference: