

FISKE BROTHERS REFINING CO -- LUBRIPLATE NO. 130-A NO. 130-AA -- 9150-00-857-9079

=====
Product Identification
=====

Product ID:LUBRIPLATE NO. 130-A NO. 130-AA
MSDS Date:01/01/1997
FSC:9150
NIIN:00-857-9079
Status Code:A
MSDS Number: CKSGD
=== Responsible Party ===
Company Name:FISKE BROTHERS REFINING CO
Address:1500 OAKDALE AVE
Box:8038
City:TOLEDO
State:OH
ZIP:43605-3843
Country:US
Info Phone Number:419-691-2491
Emergency Phone Num:800-255-3924 CHEM-TEL
Preparer's Name:JAMES KONTAK
CAGE:9N579

=== Contractor Identification ===
Company Name:FISKE BROTHERS REFINING CO
Address:1500 OAKDALE AVE
Box:City:TOLEDO
State:OH
ZIP:43605
Country:US
Phone:419-691-2491
CAGE:9N579
Company Name:INDUSTRIAL SUPPLY CORP
Address:1905 WESTWOOD AVE
Box:6356
City:RICHMOND
State:VA
ZIP:23230
Country:US
Phone:804-355-8041
Contract Num:SP0450-00-M-C857
CAGE:6A908

=====
Composition/Information on Ingredient
=====

ts =====

Ingred Name:NON-HAZARDOUS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS MAY VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF

TOXICITY, BUT MINUTE

AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Effects of Overexposure:SKIN AND EYE IRRITATION, MILD TO SEVERE PULMONARY INJURY.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH WITH SOAP AND WARM WATER

. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF THE APPEARANCE OR ITS SIZE, CONSULT PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF EFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT IMMEDIATELY REMOVE FROM EXPOSURE AND CALL PHYSICIAN. INGESTION: IF INGESTED, CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:=-204.4C, 400.F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY(FOG)

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONTINUED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

=====

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWER S AND WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRY BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED

Ventilation:LOCAL EXHAUST AND MECHANICAL GENERAL USED TO CAPTURE FUMES AND VAPORS.

Protective Gloves:OIL-RESISTANT IF NEEDED

Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES

Other Protective Equipment:OIL RESISTANT APRON IF NEEDED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.94-0.96

Evaporation Rate & Reference: