

ALCO-METALUBE CO. -- ALCO METALUBE -- 9150-00-530-6814

=====  
===== Product Identification =====

Product ID:ALCO METALUBE  
MSDS Date:02/25/1998  
FSC:9150  
NIIN:00-530-6814  
Status Code:A  
MSDS Number: CKXQM  
=== Responsible Party ===  
Company Name:ALCO-METALUBE CO.  
Address:7841 ALABAMA ST SUITE 2  
City:CANOGA PARK  
State:CA  
ZIP:91304-4953  
Country:US  
Info Phone Num:818-347-9421  
Emergency Phone Num:818-347-9421  
CA  
GE:58100

==== Contractor Identification ===  
Company Name:ALCO-METALUBE CO.  
Address:7841 ALABAMA ST SUITE 2  
Box:City:CANOGA PARK  
State:CA  
ZIP:91304-4953  
Country:US  
Phone:818-347-9421  
CAGE:58100  
Company Name:RADIAN INTL LLC  
Address:8501 N MOPAC BLVD  
Box:201088  
City:AUSTIN  
State:TX  
ZIP:78720-1088  
Country:US  
Phone:512-419-5224  
Contract Num:SP0450-00-D-4021  
CAGE:29913

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBONS  
Other REC Limits:NONE  
OSHA PE

L:NA  
ACGIH TLV:NA

Ingred Name:PB (MEETS EPA LIMITS)  
CAS:7439-92-1  
RTECS #:OF7525000  
Other REC Limits:NONE  
OSHA PEL:NA  
ACGIH TLV:NA  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SORES-OPEN WOUNDS. POSSIBLE SKIN RASH  
IF ALLOWED TO REMAIN FOR PROLONGED TIME. PROTECT EYES FROM POSSIBLE  
"THROW."  
Explanation of Carcinogenicity:NIL. NTP-NA. IARC MONOG  
RAPH-NA. OSHA  
REGULATED-NO.  
Effects of Overexposure:NONE  
Medical Cond Aggravated by Exposure:NONE

=====  
===== First Aid Measures =====

First Aid:DRINK MILK OR WATER TO DILUTE-OBTAIN MEDICAL ADVICE IF  
INGESTED. THROUGH WASHING WHERE AFFECTED, ESPECILALLY EYES.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:~225.C, 437.F  
Extinguishing Media:DRY CHEMICAL, FOAM, LIGHT WATER OR MIST SPRAY.  
Fire Fighti  
ng Procedures:AVOID STRONG DIRECT STREAM SO AS TO NOT  
SPREAD. NONE (HIGH HEAT LUBRICANT).

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SHOVEL-SCRAPE EXCESS-WASH/DILUTE WITH PAINT  
THINNER OR INDUSTRIAL STRENGTH CLEANERS FOLLOWING CONTAINER  
PRESCRIBED PRECAUTIONS. EYE PROTECTION OPTIONAL-SHOULD BE USED AS  
INTENDED.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:GLOVES, LONG SLE

EVES OPTIONAL-WASH

HANDS THOROUGHLY AFTER USE AND BEFORE EATING.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:NA

Protective Gloves:OPTIONAL

Eye Protection:OPTIONAL

Other Protective Equipment:NOT NECESSARY.

Work Hygienic Practices:AVOID INGESTION-WASH AFTER USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>315.6C, 600.F

Melt/Freeze

Pt:>371.1C, 700.F

Vapor Pres:NEG.

Vapor Density:NA

Spec Gravity:2.3

Evaporation Rate & Reference:NEG. (BUTYL ACETATE=1)

Solubility in Water:NON-SOLUBLE

Appearance and Odor:LIGHT GREEN-BUTTERY, LITTLE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

HYDROGEN PEROXIDE-OXIDIZERS.

Stability Condition to Avoid:LOSES SOME CO2 ABOVE 400 F.

Hazardous Decomposition Products:PROLONGED EXTREME HEAT-CARBON MONOXIDE/DIOXIDE.

Condi

tions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE AS PROSCRIBED BY LOCAL CIVIC GUIDESLINES-CONTAONERS SHOULD NOT BE RE-USED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate

and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.