View NSN Online: https://aerobasegroup.co.il/nsn/9150-00-482-6884

DOW CORNING CORPORATION -- DOW CORNING (R) 3451 CHEMICAL RESISTANT BEARING GREASE -- 9150-00-482-6884

Product ID:DOW CORNING (R) 3451 CHEMICAL RESISTANT BEARING GREASE MSDS Date:11/09/2000 FSC:9150 NIIN:00-482-6884 Status Code:A **MSDS Number: CLBFY** === Responsible Party === Company Name: DOW CORNING CORPORATION Address:3901 SOUTH SAGINAW ROAD Box:997 City:MIDLAN D State:MI ZIP:48686-0997 Country:US Info Phone Num:517-496-6000/517-496-6315 Emergency Phone Num:517-496-5900 Resp. Party Other MSDS Num.:01974220 Chemtrec Ind/Phone:(800)424-9300 CAGE:5D028 === Contractor Identification === Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: MCKEOWN ROBERT CO. INC. Address:111 CHAMBERS BROOK RD. Box:City:SOMERVILLE State:NJ ZIP:08876 Country:US Ρ

hone:908-218-9000 Contract Num:SP0450-01-M-LA57 CAGE:7B953

Ingred Name:NONE PRESENT. THIS IS NOT A HAZARDOUS MATERIAL AS DEFINED IN THE OSHA HAZARD COMMUNICATION STANDARD. = Wt:100. Code:F

Health Hazards Acute and Chronic:ACUTE EFFECTS: EYE-DIRECT CONTACT MAY CAUSE TEMPORARY REDNESS AND DISCOMFORT. SKIN-NO SIGNIFICANT IRRITATION EXPECTED FROM A

SINGLE SHORT-TERM EXPOSURE.

INHALATION-NO SIGNIFICANT EFFECTS FROM A SINGLE SHORT-TERM EXPOSURE. ORAL-LOW INGESTION HAZARD IN NORMAL USE.

PROLONGED/REPEATED EXPOSURE EFFECTS: SKIN-NO KNOWN APPLICABLE INFORMATION. INHLATION-NO KNOWN APPLICABLE INFORMATION. ORAL-NO KNOWN APPLI CABLE INFORMATION.

Effects of Overexposure:NO KNOWN APPLICABLE INFORMATION. Medical Cond Aggravated by Exposure:NO KNOWN APPLICABLE INFORMATION.

============

First Aid:EYE: IMMEDIATELY FLUSH WITH WATER. SKIN: NO FIRST AID SHOULD BE NEEDED. INHALATION: NO FIRST AID SHOULD BE NEEDED. ORAL: NO FIRST AID SHOULD BE NEEDED.

Flash Point:SOLID

Extinguishing Media:ON LARGE FIRES USE DRY CHEMICAL, FOAM, OR WATER SPRAY. ON SMALL FIRES USE CARBON DIOXIDE (CO2), DRY CHEMICAL. OR WATER SPRAY. WATER CAN BE USED TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedur

es:SELF-CONTAINED BREATHING APPAATUS & PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING LARGE FIRES INVOLVING CHEMICALS. DETERMINE THE NEED TO EVACUATE OR ISOLATE THE AREA ACCORDING TO YOUR LOCAL EMERGENCY PLAN. USE WATER SPRAY TO KEEP FIRE EXPOSED CONTAINERS COOL.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:OBSERVE ALL PERSONAL PROTECTION EQUIPMENT RECOMMENDATIONS DESCRIBED IN FIRE FIGHTING/ CONTROL MEASURE

SECTIONS. WIPE UP OR SCRAPE UP & CONTAIN FOR SALVAGE OR DISPOSAL. CLEAN AREA AS APPROPIATE SINCE SO ME SILICONE MATERIALS, EVEN IN SMALL AMOUNTS, MAY PRESENT A SLIP HAZARD. FINAL CLEANING MAY REQUIRE USE OF STEAM, SOLVENTS OR DETERGENT. DISPOSE OF SATURATED ABSORBENT/CLEANING MATERIAL APPROPIATELY.

Handling and Storage Precautions: USE WITH ADEQUATE VENTILATION. THIS MATERIAL MAY FORM HIG

HLY TOXIC VAPORS OF TRIFLUOROPROPIONALDEHYDE IF HEATED IN AIR ABOVE 300F (149C). PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE. ABOVE 482F/250C CAN PRODUCE HIGHLY TOXIC GASEOUS COMPONDS SUCH AS HYDROCARBON FLUORIDE & PERFLUOROHYDROCARBONS. Other Precautions:PROVIDE GOOD VENTILATION OR RESPIRATOR IF PROBABILITY OF EXCEEDING 482F/250C. AVOID CONTAMINATION OF TOBACCO PRODUCTS. AVOID EYE CONTACT. USE REASONABLE CARE & STORE AWAY FROM OXIDIZING MATERIALS.

Respiratory Protection:NO RESPIRATORY PROTECTION SHOULD BE NEEDED. Ventilation:LOCAL VENTILATION: NONE SHOULD BE NEEDED. GENERAL VENTILATION: RECOMMENDED.

Protective Gloves: NO SPECIAL PROTECTION NEEDED. Eye Protection: USE PROPER PROTECTION-SAFETY GLASSES AS A MINIMUM.

Work Hygienic Practices: WASHING AT MEALTIME AND END OF SHIFT IS

ADEQUATE. AVOID EYE CONTACT. USE REASONABLE CARE.

Supplemental Safety and Health

MSDS NO.: 01974220. GENERIC

DESCRIPTION: FLUOROSILICONE GREASE.

PHYSICAL FORM: GREASE. COLOR: WHITE. ODOR: SLIGTHT ODOR. NFPA PROFILE: HEALTH=2, FLAMMIBILITY=1, INSTABILITY/REACTIVITY=0. NOTE: NFPA=NA TIONAL FIRE PROTECTION ASSOCIATION.

HCC:N1 Vapor Pres:N/D Vapor Density:N/D Spec Gravity:1.4 Viscosity:N/D Appearance and Odor:GREASE, WHITE, SLIGHT ODOR.

Stability Indicator

/Materials to Avoid:YES
OXIDIZING MATERIAL CAUSE A REACTION.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CARBON OXIDES AND TRACES OF
INCOMPLETELY BURNED CARBON COMPOUNDS. SILICON DIOXIDE. FLUORINE COMPOUNDS. FORMALDEHYDE.

Toxicological Information: ACUTE TOXICOLOGY DATA FOR PRODUCT: COMPLETE INFORMATION IS NOT YET AVAILABLE. COMPONENT TOXICOLOGY INFORMATION: INHALATION OF FUMES FROM FIRE DE

COMPOSITION OF

POLYTETRAFLUOROETHYLENE (TEFLON) IS KNOWN TO CAUSE POLYMER FUME FEVER. THIS MATERIAL MAY FORM HIGHLY TOXIC VAPORS OF TRIFLUOROPROPIONALDEHYDE IF HEATED IN AIR ABOVE 300 (DEGREES) F (149 DEGREES C). PROVIDE VENTILATION TO CONTROL VAPOR EXPOSU RE (INHALATION GUIDELINES HAVE NOT BEEN ESTABLISHED). SPECIAL HAZARD INFORMATION ON COMPONENTS: NO KNOWN APPLICABLE INFORMATION.

Ecological:ENVIRON

MENTA; FATE AND DISTRIBUTION: NO SPECIFIC INFORMATION IS AVAILABLE. ENVIRONMENTAL EFFECTS: NO SPECIFIC INFORMATION IS AVAILABLE. FATE AND EFFECTS IN WASTE WATER TREATMENT PLANTS: NO SPECIFIC IN FORMATION IS AVAILABLE. ECOTOXICITY CLASSIFICATION CRITERIA: HAZARD PARAMETERS (LC50 OR EC50)-ACUTE AQUATIC TOXICITY (MG/L), HIGH 1 & 100. ACUTE TERRESTIAL TOXICITY, HIGH 100 & 2000.

Waste Disposal Methods:WHEN A DECISION IS MADE TO DISCARD THIS MATERIAL, AS RECEIVED, IT IS CLASSIFIED AS A HAZARDOUS WASTE? NO. STATE OR LOCAL LAWS MAY IMPOSE ADDITIONAL REGULATORY REQUIREMENTS REGARDING DISPOSAL.

Transport Information:DOT ROAD SHIPMENT INFORMATION (4 CFR 172.101): NOT SUBJECT TO DOT. OCEAN SHIPMENT (IMDG): NOT SUBJECT TO IMDG CODE. AIR SHIPMENT (ICAO): NOT SUBJECT TO ICAO REGULATIONS. CALL DOW CORNING TRANSPORT SARA Title III Information:SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES: NONE. SECTION 304 CERCLA HAZARDOUS SUBSTANCES: NONE. SECTION 312 HAZARD CLASS: ACUTE-NO, CHRONIC-NO, FIRE-NO, PRESSURE-NO, REACTIVE-NO. SECTION 313 TOXIC CH EMICALS: NONE PRESENT OR NONE PRESENT IN REGULATED QUANTITIES.

Federal Regulatory Information:CONTENTS OF THIS MSDS COMP LY WITH THE

OSHA HAZARD COMMUNICATION STANDRAD 29 CFR 1910.1200. TSCA STATUS: ALL CHEMICAL SUBSTANCES IN THIS MATERIAL ARE INCLUDED ON OR EXEMPTED FROM LISTING ON THE TSCA IN VENTORY OF CHEMICAL SUSBSTANCES.

State Regulatory Information:CALIFORNIA: WARNING: THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED BY THE STATE OF CALIFORNIA UNDER THE SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65) AS BEING KNOWN TO CAUSE CANCER, BIRTH DEFECTS OR

OTHER REPRODUCTIVE HARM. NONE KNOWN. MASSACHUSETTS: NO INGREDIENTS REGULATED BY MA RIGHT-TO-KNOW LAW PRESENT. NEW JERSEY: 63148-56-1, >60%, TRIFLUOROPROPYLMETHYL SILOXAN E, TRIMETHYL-TERMINATED. 9002-84-0, 30.00-60.00, POLYTETRAFLUOROETHYLENE. PENNSYLVANIA: 63148-56-1, >60%, TRIFLUOROPROPYLMETHYL SILOXANE, TRIMETHYL-TERMINATED. 9002-84-0, 30.00-60.00, POLYTETRAFLUOROETHYLENE.

Disclaimer (provided wit

h this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.