

SIRCHIE FINGER PRINT LABORATORIES INC -- FINGERPRINT INK 230/23IT -- 7510-00-148-3162
===== Product Identification =====

Product ID:FINGERPRINT INK 230/23IT
MSDS Date:05/30/1988
FSC:7510
NIIN:00-148-3162
Status Code:A
MSDS Number: CLBJF
=== Responsible Party ===
Company Name:SIRCHIE FINGER PRINT LABORATORIES INC
Address:100 HUNTER PLACE
City:YOUNGSVILLE
State:NC
ZIP:27596
Country:US
Info Phone
Num:919-554-2244
Emergency Phone Num:0000000000
CAGE:94514
=== Contractor Identification ===
Company Name:SIRCHIE FINGER PRINT LABORATORIES INC
Address:100 HUNTER PLACE
Box:City:YOUNGSVILLE
State:NC
ZIP:27596
Country:US
Phone:919-554-2244
CAGE:94514

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC HYDROCARBON SOLVENT
CAS:64742-55-8
RTECS #:PY8036500

Ingred Name:HYDROTREATED HEAVY NAPHTENIC DISTILLATE, PETROLEUM

===== Hazards Identifi

cation =====

Health Hazards Acute and Chronic:EXCESSIVE INHALATION MAY CAUSE HEADACHE, DIZZINESS, DROWSINESS AND NAUSEA. BECAUSE OF IT'S DEFATTING ACTION ON THE SKIN, THE SOLVENT IN THIS PRODUCT MAY CAUSE IRRITATION AND DERMATITIS. EYE IRRITATION IS ALSO POSSIBLE.

Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE RESTORE BREATHINGCALL PHYSICIAN. EYES: FLUSH WITH WATER FOR 15 MINUTES CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. REMOVE SOILED CLOTHING.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:WATER SPRAY MAY BE EFFECTIVE
Unusual Fire/Explosion Hazard:ISOLATE FROM EXTREME HEAT AND OR OPEN FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA. ADD ABSORBENT AND SCOOP INTO DISPOSAL CONTAINER. WASH AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF MIST CORE IS HIGH.
Protective Gloves:REQUIRED FOR PROLONGED USE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=243.3C, 470.F
B.P. Text:470-650 F
Vapor Density:+AIR
Evaporation Rate & Reference:BUTYL ACETATE SLOWER
Appearance and Odor:BLACK PASTE OLEORESINOUS
Percent Volatiles

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATE IN APPROVED MANNER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America

in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.