View NSN Online: https://aerobasegroup.com/nsn/8040-01-057-0092

Product ID: EASYPOXY K-20 PART A ADHESIVE MSDS Date:07/01/1997 FSC:8040 NIIN:01-057-0092 Status Code:A Kit Part:Y MSDS Number: CLGSR === Responsible Party === **Company Name: CONAP INC** Address:1405 BUFFALO STREET City:OLEAN State:NY ZIP:14760-1139 Country:US Info Phone Num:716-372-9650/376-7887 Emergency Phone Num:1-800-424-9300 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:16245 === Contractor Identification === Company Name: CONAP INC., WHOLLY OWNED SUBSIDIARY OF CYTEC INDUSTRIES INC. Address:1405 BUFFALO STREET Box:City:OLEAN State:NY ZIP:14760 Country:US Phone:716-372-9650 CAGE:16245

Ingred Name:.ALPHA.-QUARTZ CAS:14808-60-7 RTECS #:VV7330000 Minumum % Wt:25. Maxumum % Wt:30. OSHA PEL:SEE TABLE Z- 3 ACGIH TLV:0.1 MG/M3

Ingred Name:ACTICEL CAS:7631-86-9 &It; Wt:4.

Ingred Name:1,2,3-PROPANETRIOL CAS:56-81-5 RTECS #:MA8050000 &It; Wt:1. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: EPOXYRESIN(S)

LD50 LC50 Mixture:NONE

Health Hazards Acute and Chronic:MAY CAUSE ALLERGIC SKIN REACTION MAY CAUSE EYE IRRITATION. CHRONIC TOXICITY HAZARD. CONTAINS MATERIAL WHICH MAY CAUSE LUNG DAMAGE. POSSIBLE CANCER HAZARD BASED ON

LABORATORY ANIMAL TESTS. RISK DEPENDS ON DURATION AND LEVEL OF EXPOSURE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:OVEREXPOSURE TO VAPOR DURING HEAT CURING MAY CAUSE IRRITATION OR INJURY OF THE RESPIRATORY TRACT AND EYE IRRITATION. DIRECT CONTACT WITH THIS MATERIAL MAY CAUSE MILD EYE IRRITATION. INHALATION OVEREX POSURE TO THIS PRODUCT MIXTURE IS NOT LIKELY UNDER NORMAL USE CONDITIONS DUE TO ITS PHYSICAL FORM. Medical Cond Aggravated by Exposure:NON E

First Aid:IN CASE OF SKIN CONTACT, WASH AFFECTED AREAS WITH SOAP AND PLENTY OF WATER. OBTAIN MEDICAL ATTENTION. IN CASE OF EYE CONTACT, IMMEDIATELY IRRIGATE WITH PLENTY OF WATER FOR 15 MINUTES. MATERIAL IS NOT EXPECTED TO BE HARMFUL IF INHALED. IF INHALED, ERMOVE TO FRESH AIR.

Flash Point Method:TCC Flash Point:=93.3C, 200.F Autoignition Temp:Autoignition Temp Text:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. USE WATER TO KEEP CONTAINERS COOL. WEAR SELF CONTAINED POSITIVE PRESSURE BREATHING APPARATUS. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:WEAR IMPERVIOUS BOOTS. COVER SPILLS WITH SOME INERT ABSORBENT MATERIAL; SWE

EP UP AND PLACE IN A WASTE DISPOSAL CONTAINER. FLUSH AREA WITH WATER. WHERE EXPOSURE LEVEL IS NOT KNOWN, WEAR NIOSH APPROVED POSITIVE PRESSURE SELF CONTAINED RESPIRATOR. WHERE EXPOSURE LEVEL IS KNOWN, WEAR NIOSH APPROVED RESPIRATOR SUITABLE FOR LEVEL OF EXPOSURE. Neutralizing Agent:NONE

Handling and Storage Precautions: AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING. Other Precautions: NONE

====== Exposure Controls/Personal Protection ==========

- Respiratory Protection: USE RESPIRATOR APPROVED BY NIOSH FOR THE MATERIAL AND LEVEL OF EXPOSURE. A FULL FACEPIECE RESPIRATOR WILL PROVIED EYE AND FACE PROTECTION.
- Ventilation: GOOD ENCLOSURE AND LOCAL EXHAUST VENTILATION SHOULD BE PROVIDED TO CONTROL EXPOSURE.
- Protective Gloves: BARRIER CREAMS MAY BE USED IN CONJUNCTION WITH THE GLOVES.
- Eye Protection:WEAR EYE PROTECTION SUC
- H AS CHEMICAL SPLASH PROOF
- GOGGLES OR FACE SHIELD.

Other Protective Equipment:PROTECTIVE CLOTHING SUCH AS IMPERVIOUS GLOVES, APRON, WORKPNTS, LONG SLEEVE WORK SHIRT, OR DISPOSABLE COVERALLS ARE RECOMMENDED TO PREVENT SKIN CONTACT.

Work Hygienic Practices: EYEWASH EQUIPMENT AND SAFETY SHOWER SHOULD BE PROVIDED IN AREAS OF POTENTIAL EXPOSURE.

Supplemental Safety and Health

SHOWER AFTER COMPLETION OF WORKSHIFT.

oiling Pt:B.P. Text:NONE Melt/Freeze Pt:M.P/F.P Text:NONE Decomp Temp:Decomp Text:NONE Vapor Pres:NONE Spec Gravity:1.28 Evaporation Rate & amp; Reference: