View NSN Online: https://aerobasegroup.co.il/nsn/6750-01-097-0773

EASTMAN KODAK COMPANY -- 812 1188,PT B,KODAK T-MAX 100 DIRECT POSITIVE (SEE SUPPL) -- 6750-01-097-0773

Product ID:812 1188, PT B, KODAK T-MAX 100 DIRECT POSITIVE (SEE SUPPL) MSDS Date:03/09/2001 FSC:6750 NIIN:01-097-0773 Status Code:A Kit Part:Y **MSDS Number: CLHHP** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTE R State:NY ZIP:14650 Country:US Info Phone Num:800-242-2424 Emergency Phone Num:716-722-5151 Preparer's Name:NOT PROVIDED CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Minumum % Wt:80. Maxumum % Wt:85. Other REC Limits:NOT PROVIDED Code:F Code:F

Ingred Name:POLYETHYLENE GLYCOL CAS:25322-68-3 RTECS #:TQ3500000 Minumum % Wt:5. Maxumum % Wt:10. Other REC Limits:NOT PROVIDED OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name:POTASSIUM SULFITE CAS:10117-38-1 RTECS #:WT3530000 Minumum % Wt:5. Maxumum % Wt:10. Other REC Limits:NOT PROVIDED OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name:DIMETHYLAMINE BORANE CAS:74-94-2 RTECS #:IP9450000 < Wt:.1 Other REC Limits:NOT PROVIDED OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

LD50 LC50 Mixture:NOT PROVIDED Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: EXPECTED LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE G AS IS IRRITATING TO RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS

MAY EXPERIENCE DIFFICULT BREATHING. EYES: CAUSES IRRITATION. SKIN: MATERIAL HAS LOW POTENTIAL TO CAUSE ALLERGIC SKI N REACTIONS; HOWEVER, CASES OF HUMAN SKIN SENSITIZATION HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF GASTROINTESTINAL TRACT.

Explanation of Carcinogenicity:(IARC): HYDROQUINONE, SULFUR DIOXIDE, SOME SULFITES, BISULFITES AND METASULFITES, GROUP 3; NOT CLASSIFIABLE. (ACGIH): HYDROQUIN

ONE, A3; CONFIRMED ANIMAL

CARCINOGEN WITH UNKNOWN RELEVANCE HUMANS. - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE

Effects of Overexposure:INHALATION: IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO RESPIRATORY TRACT. EYES: CAUSES IRRITATION. SKIN: INGESTION: MAY C AUSE IRRITATION OF GASTROINTESTINAL TRACT. Medical Cond Aggravated by Exposure:

SOME ASTHMATICS, HYPERSENSITIVE OR

SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA.

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTEN TION IF SY

MPTOMS OCCUR. SKIN: WASH WITH SOAP AND

WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCO NSCIOUS PERSON.

Flash Point:NONFLAMMABLE

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRO

DUCE HAZARDOUS DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard:NONE

======================================
Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL C ONTAMINATION. Neutralizing Agent: NONE
======================================
 Handli ng and Storage Precautions:KEEP CONTAINER CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES. Other Precautions:AVOID BREATHING MIST. AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.
======================================
Respiratory Protection:NONE SHOULD BE NEEDED. A RESPIRATOR SHOULD BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE OR HAVE BEEN RELEASED
. RESPIRATOR TYPE: ACID GAS. IF RESPIRATORS ARE USED, A PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANCE WITH OSHA STANDARD 29 CFR 1910.134.
Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.
Protective Gloves:FOR PROLONGED OR REPEATED SKIN CONTACT, IMPERVIOUS GLOVES SHOULD BE WORN.
Eye Protection:WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES). Other Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER
Work Hygienic Practices: IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE SKIN CONTACT.
Supplemental Safety and Health CONTD FROM PRODUCT ID: FILM REDEVELOPER. THIS IS A KIT. THE OTHER MSDS SERIAL NUMBER: CLHHN.
======================================
HCC:B3 NRC/State Lic Num:NOT RELEVANT

Boiling Pt:>100.C, 212.F

Melt/Freeze Pt:M.P/F.P Text:NOT PROVIDED

Decomp Temp:Decomp Text:NOT PROVIDED Vapor Pres:68F: 24 MBAR (18 MM

HG) Vapor Density:0.6 Spec Gravity:1.08 pH:7.0 Viscosity:NOT PROVIDED Evaporation Rate & amp; Reference:NOT PROVIDED Solubility in Water:APPRECIABLE Appearance and Odor:WHITE, WAXY LIQUID, SLIGHT ODOR. Percent Volatiles by Volume:80-85 WT Corrosion Rate:NOT PROVIDED

Stability Indicator/Materials to Avoid:YES STRONG ACIDS. Stability Condition to Avoid:NOT PROVIDED Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE

SULFUR DIOXIDE.

Toxicological Information:INHALATION: EXPECTED LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE G AS IS IRRITATING TO RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: CAUSES IRRITATION. SKIN: MATERIAL H

AS

LOW POTENTIAL TO CAUSE ALLERGIC SKI N REACTIONS; HOWEVER, CASES OF HUMAN SKIN SENSITIZATION HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF GASTROINTESTINAL TRACT.

Ecological:THE FOLLOWING PROPERTIES ARE ESTIMATED FROM THE COMPONENTS OF THE PREPARATIONS. POTENTIAL TOXICITY: FISH LC50 MG/L: >100. DAPHNID EC50 MG/L: >100. ALGAL IC50 MG/L: >100. ORGANICS REA DILY DEGRAD ABLE (>70%): NO. POTENTIAL BIOACCUMULATION: LOG POW 100.

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EV EN AFTER CONTAINER IS EMPTIED.

Transport Informat ion:FOR TRANSPORTATION INFORMATION REGARDING THIS PRODUCT CALL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE: (716) 722-2400 BETWEEN 8 A.M. AND 5 P.M. (EASTERN STANDARD TIME), MONDAY THROUGH FRIDAY.

SARA Title III Information:CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372:

NONE.

Federal Regulatory Information:NOT PROVIDED

State Regulatory Information:MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: NONE - MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Ame rica in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.