View NSN Online: https://aerobasegroup.com/nsn/4610-01-266-7531 VILLAGE MARINE TEC -- CHEMICAL #3 ______ MSDS Safety Information _____ FSC: 4610 NIIN: 01-266-7531 MSDS Date: 04/14/1993 MSDS Num: CLHHT Product ID: CHEMICAL #3 MFN: 01 Kit Part: Y Responsible Party Cage: 62144 Name: VILLAGE MARINE TEC Address: 2000 W 135TH ST City: GARDENA CA 90249 Info Phone Number: 310-516-9911 Emergency Phone Number: 310-516-9911 ______ Item Description Information ______ Item Manager: S9C Item Name: PARTS KIT, WATER CHE Unit of Issue: KT UI Container Qty: Z _____ Ingredients ______ Name: *** PROPRIETARY *** _____ _____ _____ Health Hazards Data ______ LD50 LC50 Mixture: RAT, INTRAVENOUS, LD50: 115 MG/KG.

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: TARGET ORGANS: LUNGS. ACUTE EFFECTS: EYE, SKIN, AND

GSTROINTESTINAL IRRITATION. CHRONIC: UNKNOWN.

Explanation Of Carcinogenicity: SUSPECTED CANCER AGENT: NO. THIS PRODUCT IS NOT

CONSIDERED A CARCINOGEN BY NTP, IARC, OR OSHA.

Signs And Symptions Of Overexposure: I

NHALATION OF DUST OR MISTS MAY CAUSE

IRRITATION TO THE RESPIRATORY TRACT. EYE CONTACT MAY CAUSE IRRITATION OR BURNING SENSTATION. REPEATED OR PROLONGED CONTACT WITH SKIN MAY CAUSE IRRITATION AT POINT OF CONTACT. INGESTION MAY CAUSE GASTROINTESTINAL TRACT IRRITATION. SKIN ABSORPTION SHOULD NOT OCCUR.

First Aid: IF SPILLED ON SKIN OR EYES, IMMEDIATELY DECONTAMINATION WITH RUNNING WATER. REMOVE EXPOSED/SOILED CLOTHING, D NOT CONTAMINATE EYES. VICTIM & Amp; RECUSERS MUST SEEK IMMEDIATE M

EDICAL ATTENTION. IF CHEMICAL IS IN EYES. OPEN

EYES WHILE UNDER GENTLE RUNNING WATER. USE SUFFICIENT FORCE TO OPEN EYELIDS. ROLL EYES. FLUSH FOR 15 MINS. IF CHEMICAL IS INHALED, REMOVE VICTIM TO FRESH AIR & ARTIFICIAL RESPIRA TION TO SUPPORT VITAL FUNCTIONS. REMOVE OR COVER GROSS CONTAMINATION TO AVOID EXPOSURE TO RESCUERS. IF CHEMICAL IS SWALLOWED, RINSE MOUTH WITH WATER. GIVE VICTIM 2-3 GLASSES OF WATER TO DRINK TO DILUT E THE MATERIAL.

Handling and Disposal

Spill Release Procedures: NOTIFY SAFETY PERSONNEL OF SODIUM METABISULFITE SPILLS. PROVIDE ADEQUATE VENTILATION. CLEAN-UP PERSONNEL NEED PROTECTION AGAINST INHALATION OF DUST OR MIST. MINIMUM (RUBBER GLOVES & EMP); RUBBER APRON, SPLA SH GOGGLES OR SAFETY GLASSES). SWEEP UP OR VACUUM MATERIAL, AVOIDING DUSTING CONDITIONS, & ED ACE IT IN AN APPROPIATE CONTAINER FOR RECLAMATION OR DISPOSAL. "

SEE OTHER INFO"

Waste Disposal Methods: WASTE DISPOSAL MAY BE IN ACCORDANCE WITH APPROPIATE FEDERAL, STATE & DISPOSED OF BY TREATEMNT AT A PERMITTED FACILITY OR AS ADVISED BY YOUR LOCAL HAZARDOUS WASTE REGULATORY AUTHORITY.

Handling And Storage Precautions: STORE SODIUM METABISULFITE IN CLOSED CONTAINERS IN A COOL, DRY, WELL-VENTILATED AREA SEPARATE FROM OXIDIZING AGENTS, ACIDS, AND MOISTURE. PROTECT IT FROM PH YSICAL DAMAGE.

Other Precautions: UES GOOD HOUSEKEEPING PARCTICES TO PREVENT ACCUMULATION OF DUST OR SOLUTION MIST. DO NOT BREATHE DUSTS OR MISTS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. MINIMIZE CONTACT WITH SKIN BY WEARING PROPE R GLOVES AND SPRON AND FOLLOW GOOD PERSONAL HYGIENE. DO NOT INGEST THIS MATERIAL. KEEP IN TIGHTLY CL OSED CONTAINER.

Fire and Explosion Hazard Information

========

Flash Point Text: NONFLAMMABLE

Extinguishing Media: AVOID USING WATER UNLESS FLOODING AMOUNTS ARE USED;

OTHERWISE USE CARBON DIOXIDE, DRY CHEMICAL, OR DRY SAND.

Fire Fighting Procedures: FIRE FIGHTERS MUST USE SELF CONTAINED BREATHING APPARATUS AND WEAR FULLY PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard: TEMPERATURES ABOVE 302F(150C) CAUSE THIS

MATERIAL TO DECOMPOSE, YIELDING TOXIC & CORROSIVE SULFUR DIOXIDE GAS

& amp; SODIUM SULFIDE. THE LATER IS AN EXPLOSIVE HAZARD

AND IS STRONGLY

ALKALINE WHEN IT IS IN THE PRESENCE OF WATER.

Control Measures

Respiratory Protection: USE NIOSH APPROVED RESPIRATORS IF VENTILATION IS INADEQUATE TO CONTROL DUSTS OR MISTS.

Ventilation: USE WITH ADEQUATE VENTILATION. USE A MECHANICAL FAN OR VENT AREA TO OUTSIDE.

Protective Gloves: WEAR CHEMICALLY IMPERVIOUS GLOVES WHICH ARE RESISTANT TO BASIC MATERIALS.

Eye P

rotection: SAFETY GLASSES SHOULD ALWAYS BE WORN. SPLASH GOGGLES OR FACESHIELD.

Other Protective Equipment: WEAR A CHEMICALLY RESISTANT APRON AND BOOTS TO PREVENT SPLASHES FROM CONTACTING THE BODY. EYE WASH STATION & WASHING FACILITIES SHOULD BE AVAILABLE TO AREAS OF USE & HANDLING.

Work Hygienic Practices: AVOID GETTING CHEMICALS ON YOU OR IN YOU. WASH HANDS AFTER HANDLING CHEMICALS. DO NOT EAT OR DRINK WHILE HANDLING CHEMICALS.

Supplemental Safety and Health: ITEM IS A THREE PART KIT. S

EE MSDS SERIAL#

CLHGW AND CLHHF. END ITEM IDENTIFICATION: 1095-00-270-6019.

Physical/Chemical Properties

HCC: C3

Boiling Point: =150.6C, 303.F B.P. Text: DECOMPOSES Melt/Freeze Pt: =150.C, 302.F M.P/F.P Text: DECOMPOSES

Spec Gravity: 1.4 PH: 4.3 (1% SOLN)

Solubility in Water: @16C, 30

Appearance and Odor: WHITE POWDER OR CRYSTALS. PUNGENT SULFUR DIOXIDE ODOR.

Reactivity Data
Stability Indicator: YES Materials To Avoid: BASES, STRONG OXIDIZING MATERIALS. Hazardous Decomposition Products: AVOID CONTACT WITH INCOMPATIBLE MATERIALS. HEAT FROM FIRE MAY CAUSE PRODUCT TO DECOMPOSE, PRODUCING TOXIC GASES. Hazardous Polymerization Indicator: NO
Toxicological Information
======================================
Ecological Information
HSDS Transport Information
Transport Information: DOT CLASS: ORM-B. UN REGISTER: NA2693.
== Regulatory Information
State Regulatory Information: CAL/ OSHA: NO.
Other Information
Other Information: SPILL: ABSORB SPILLED LIQUID ON VERMICULITE OR DRY SAND. CAUTIOUSLY FLUSH RESIDU WITH A LARGE AMOUNT OF WATER. SULFUR DIOXIDE FUMES CAN BE GENERATED ON CONTACT WITH WATER. ***RECOMMENDATIONS TO PHYS ICIANS: TREAT S YMPTOMS OF EXPOSURE TO PRODUCT INGREDIENTS. ****PRECAUTIONARY MEASURES: USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. THIS MATERIAL RELEASES SULFUR DIOXIDE GAS SLOWLY A T AMBIENT TEMPERATURES. *****EYE PROTECTION: CONTACT LENSES POSE A SPECIAL HAZARD, SOFT LENSES MAY
ABSORB IRRITANTS & amp; ALL LENSES MAY CONCENTRATE THEM. ====================================
rransportation information ====================================
леаронамие

Party Cage: 62144
Trans ID NO: 158063
Product ID: CHEMICAL #3

MSDS Prepared Date: 04/14/1993

Review Date: 07/31/2001

MFN: 1

Multiple KIT Number: 0

Kit Part IND: Y Review IND: Y Unit Of Issue: KT Container QTY: Z

Detail DOT Information

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail

IMO Information

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: CHEMICAL #3

Cage: 62144

Company Name: VILLAGE MARINE TEC

Street: 2000 W 135TH ST City: GARDENA CA Zipcode: 90249

Health Emergency Phone: 310-516-9911

Label Required IND: Y

Date Of Label Review: 07/31/2001

Status Code: A Origination Code: F

Eye P

rotection IND: YES

Skin Protection IND: YES Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight Contact Hazard: Slight Fire Hazard: None Reactivity Hazard: None

Hazard And Precautions: TARGET ORGANS: LUNGS. PRODUCT MAY CAUSE IRRITATION AT POINT OF CONTACT. ACUTE EFFECTS: EYE, SKIN, AND GSTROINTESTINAL IRRITATION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated

for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian e mployee of the

United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.