

ELDORADO CHEMICAL COMPANY, INC. -- REMOVER, PAINT,ALKALI F/HOT APPLICATION CL --
8010-01-380-2330

===== Product Identification =====

Product ID:REMOVER, PAINT,ALKALI F/HOT APPLICATION CL

MSDS Date:05/30/1997

FSC:8010

NIIN:01-380-2330

Status Code:A

MSDS Number: CLLCW

=== Responsible Party ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State

:TX

ZIP:78265-4837

Country:US

Info Phone Num:210-653-2060/FX2106530825

Emergency Phone Num:1-800-255-3924

Preparer's Name:ERHEST CARTER

CAGE:55208

=== Contractor Identification ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Phone:800-531-1088/ 210-653-2060

CAGE:55208

===== Composition/Information on Ingredients =====

Ingred Name:DICHLOROMETHANE

CAS:75-09-2

RTECS #:PA8050000

= Wt:40.

OSH

A PEL:SEE TABLE Z-2
ACGIH TLV:174 MG/M3;50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PHENOL
CAS:108-95-2
RTECS #:SJ3325000
= Wt:15.
OSHA PEL:19 MG/M3;5 PPM
ACGIH TLV:19 MG/M3;5 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM CHROMATE
CAS:07775-11-3
= Wt:1.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALATION ACUTE: HIGH;ABSORBED IN
LUNGS C
CHRONIC: SLIGHT. SKIN CONTACT ACUTE: CORROSIVE. SKIN
ABSORPTION. CHRONIC: SLIGHT EYE CONTACT ACUTE: HIGH; CORROSIVE TO
EYES, CHRONIC: SLIGHT.
Effects of Overexposure:INDUCES NARCOSIS, DIZZINESS, NASEA. CORROSIVE
TO SKIN. CONTACT IS PAINFUL; SKIN ABSORPTION WOULD BE UNLIKELY.
CORROSIVE TO EYES ON CONTACT; SHORT EXPOSURE. WILL CAUSE HAZY
VISION WHICH RETURNS TO NORM AL.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15
MINUTES; CONSULT
PHYSICIAN.SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO
FRESH AIR; IF UNCONSCIOUS, FIVE OXYGEN & SEEK MEDICAL
ATTENTION.INGESTION: CONTACT PHYSIC IAN IMMEDIATELY.

===== Fire Fighting Measures =====

Autoignition Temp:=648.9C, 1200.F
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:NONE
Fire Fighting Procedures:SCBA REQUIRED.
Unusual Fire/Explosion Hazard:TOXIC CHLORIDE FUMES MAY BE GENERATED BY
CONTACT WITH FLAME

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN AND CLEAN UP WITH ABSORBENT

===== Handling and Storage =====

Other Precautions:ALL MATERIALS USED IN THE MANUFACTURING HAVE BEEN CERTIFIED BY THEIR MANUFACTURER AS BEING ON THE CURRENT TSCA INVENTORY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA REQUIRED IF LIMITS EXCEEDED

Ventilation:100 FT/MIN

P

Protective Gloves:POLYETHYLENE

Eye Protection:FACE SHIELD AND GOGGLES

Other Protective Equipment:RUBBER APRON AND BOOTS

Work Hygienic Practices:DO NOT USE IN CONFINED SPACES. AVOID ALL SKIN CONTACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=48.9C, 120.F

B.P. Text:760 M M HG

Vapor Pres:380 M MM HG

Vapor Density:(AIR=1) 2.

Spec Gravity:1.1

pH:9.2

Evaporation Rate & Reference:WATER 1>1

Solubility in Water:PARTIALLY SOLUB

LE

Appearance and Odor:THICK, YELLOW LIQUID PHENOL ODOR.

Percent Volatiles by Volume:70%

===== Stability and Reactivity Data =====

STRONG ALKALIS, STRONG OXIDIZERS, AND REACTIVE METALS.

Hazardous Decomposition Products:HEAT WILL PRODUCE DICHLOROMETHANE AND AMMONIA FUMES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no man

er whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.