

FARWEST PAINT MANUFACTURING CO -- INTERIOR WIPING STAIN (WALNUT) -- 8010-00-598-7669

=====  
Product Identification  
=====

Product ID:INTERIOR WIPING STAIN (WALNUT)

MSDS Date:06/01/1992

FSC:8010

NIIN:00-598-7669

Status Code:A

MSDS Number: CLMVW

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num

:206-244-8844

Emergency Phone Num:206-941-1619

Preparer's Name:ERNEST CARTER

Chemtec Ind/Phone:(800)424-9300

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS

CAS:8032-32-4

Code:F

RTECS #:OI6180000

= Wt:55.07

ACGIH TLV:1370 MG/M3;300 PPM

=====

==== Hazards Identification =====

Effects of Overexposure:SKIN: THIS MATERIAL MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN UPON PROLONGED OR REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS CAN RESULT IN HEADACHE, DIZZINESS, NAUSEA AND LOSS OF CONSCIOUSNESS. EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.

Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.

=====  
==== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER. EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES AND SEEK MEDICAL ATTENTION. SWALLOWING: IF INGESTED DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET, AND GET MEDICAL ATTENTION. INHALATION: REMOVE VICTIM TO FRESH AIR IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-40.C, 104.F

Lower Limits:0.7%

Upper

Limits:6.0%

Extinguishing Media:FOAM, DRY CHEMICAL, ALCOHOL FOAM, WATER FOG, CO2.

Fire Fighting Procedures:FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE OR SAND AND PLACE MATERIAL INTO A CLOSED CONTAINER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED, WHEN NOT IN USE, AND PROPERLY LABELED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER-TYPE RES

PIRATOR MUST BE WORN TO

PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS.

Ventilation:GENERAL VENTILATION IS REQUIRED DURING NORMAL USE.

Protective Gloves:CHEMICAL RESISTANT NITRILE, NEOPRENE OR RUBBER GLOVES  
REQUIRED.

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN  
CONTACT. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and  
Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:307-387 F

Vapor Pres:2.6MMHG@20C

Vapor Density:HEAVIER

VOC Pounds/Gallon:508

Viscosity:10-25 SEC/#4

Evaporation Rate & Reference:FASTER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:COLORED LIQUID, MILD ODOR.

Percent Volatiles by Volume:63.69%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXID

ANTS, ACIDS, BASES AND EPOXY HARDENERS

UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES. IF PRODUCT  
CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE  
HYDROGEN GAS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON  
MONOXIDE AND TOXIC VAPORS.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W

ITH LOCAL, STATE AND

FEDERAL AGENCY, GROUND HANDLING EQUIPMENT TO PREVENT SPARKS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and as

assume responsibility for the suitability of this information to their particular situation.