View NSN Online: https://aerobasegroup.com/nsn/8040-00-117-8510

LOCTITE CORPORATION -- RTV 5145 PASTE NON-CORR RTV SEALANT 20250

MSDS Safety Information

FSC: 8040

NIIN: 00-117-8510 MSDS Date: 02/20/2000 MSDS Num: CLNWX

Product ID: RTV 5145 PASTE NON-CORR RTV SEALANT 20250

MFN: 01

Responsible Party Cage: 05972

Name: LOCTITE CORPORATION

Address: 1001 TROUT BROOK CROSSING

City: ROCKY HILL CT 06067-3910 Info Phone Number: 860-571-5100

Emergency Phone Number: 860-571-5100 Preparer's Name: ERNEST CARTER Chemtrec IND/Phone: (800)424-9300

Review Ind: Y Published: Y

Contractor Summary

Cage: 05972

Name: LOCTITE CORPORATION

Address: 1001 TROUT BROOK CROSSING

City: ROCKY HILL CT 06067-3910

Phone: 860-571-5100

====

Item Description Information

Item Manager: GSA Item Name: ADHESIVE

Unit of Issue: TU

Quantitative Expression: 00000000003OZ

UI Container Qty: 0

Ingredients

Name: POLY(DIMETHYLSILOXANE)

% low Wt: 60. % high Wt: 65.

Name: FILLER % low Wt: 25. % high Wt: 30.

Name: ALK

OXYSILANE % low Wt: 5. % high Wt: 10.

Name: SUBSTITUTED SILANE

% low Wt: 1. % high Wt: 3.

Cas: 64-17-5

RTECS #: KQ6300000 Name: ETHYL ALCOHOL

OSHA PEL: 1900 MG/M3;1000 PPM ACGIH TLV: 1880 MG/M3;1000 PPM ACGIH STEL: NOT ESTABLISHED

Cas: 67-56-1

RTECS #: PC1400000 Name: METHYL ALCOHOL

OSHA PEL: 260 MG/M3;200 PPM ACGIH TLV: 262 MG/M3;200 PPM ACGIH STEL: 328 MG/M3;250 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 500

0 LBS

Health Hazards Data

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Effects of Exposure: SKIN AND EYE IRRITANT. INGESTION MAY CAUSE BLINDNESS OR DEATH. VAPORS MAY INJURE EYES AND NERVOUS SYSTEM OR CAUSE UNCONSCIOUSNESS.

Signs And Symptions Of Overexposure: METHANOL AND ETHANOL PRODUDUCED DURING CURE MAY CAUSE HEADACHE, NAUSEA, DROWSINESS.

First Aid: INGESTION

: DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM.OBTAIN

MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. SKIN CONTACT: WIPE OFF PASTE WITH TOWEL OR CLOTH. WASH EXPOSE D AREA WITH SOAP AND WATER. EYE CONTACT: FLUSH AT LEAST 15 MINUTES WITH WATER. OBTAIN MEDICAL ATTENTION.

Handling and Disposal

Spill Release Procedures: REMOVE AOURCES OF IGNITION. MAINTAIN G

OOD

VENTILATION.SCRAPE UP SPILLED MATERIAL. STORE MATERIAL IN A WELL VENTILATED AREA AND ALLOW TO CURE TO RUBBER.

Waste Disposal Methods: FOLLWING EPA AND LOCAL REGULATIONS.

Handling And Storage Precautions: STORE IN A COOL, DRY AREA.KEEP CONTAINERS

CLOSED WHEN NOT IN USE. DO NOT USE NEAR HEAT, SPARKS, OPEN FLAME OR OTHER SOURCES OF IGNITION. AVOID SKIN AND EYE CONTACT. AVOID BREATHING VAPORS DO NOT USE N EAR HEAT, SPARKS, OPEN FLAME OR OTHER SOURCES OF IGNITION.

Fire and Explosion Hazard Information

Flash Point Method: TCC Flash Point: =38.9C, 102.F

Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL.

Control Measures

Ventilation: SUFFICIENT TO MAINTAIN VAPOR CONCENTRATION BELOW TLV.

Protective Gloves: RUBBER OR PLASTIC GLOVES.

Eye Protection: SAFE

TY GLASSES OR GOGGLES.

Physical/Chemical Properties

Vapor Pres: LESS 10MM AT 70 F

Spec Gravity: 1.1

VOC Pounds/Gallon: 3.64 VOC Grams/Liter: 40

Solubility in Water: POLYMERIZED

Appearance and Odor: TRANSLUCENT PASTE ETHANOL

Reactivity Data

Materials To Avoid: OXIDIZING AGEN TS, STRONG ACIDS, ALKALIES.

Hazardous Decomposition Products: HAZARDOUS DECOMPOSITION PRODUCTS: METHANOL

AND ETHANOL, OXIDES OF CARBON AND SILICON.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR.

HAZCOM Label

Product ID: RTV 5145 PASTE NON-CORR RTV SEALANT 20250

Cage: 05972

Company Name: LOCTITE CORPORATION Street: 1001 TROUT BROOK CROSSING

City: ROCKY HILL CT Zipcode: 06067-3910

Health Emergency Phone: 860-571-5100

Label Required IND: Y

Date Of Label Review: 10/22/2001

Status Code: A Origination Code: G

Hazard And Precautions: SKIN AND EYE IRRITANT. INGESTION MAY CAUSE BLINDNESS OR

DEATH. VAPORS MAY INJURE EYES AND NERVOUS SYSTEM OR CAUSE UNCONSCIOUSNESS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by ele ments of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.