

NOVUS INC -- NOVUS PLASTIC POLISH #1 -- 7930-00-935-3794

=====
Product Identification
=====

Product ID:NOVUS PLASTIC POLISH #1
MSDS Date:07/19/1999
FSC:7930
NIIN:00-935-3794
Status Code:A
MSDS Number: CLQQQ
=== Responsible Party ===
Company Name:NOVUS INC
Address:10425 HAMPSHIRE AVE SOUTH
City:MINNEAPOLIS
State:MN
ZIP:55438
Country:US
Info Phone Num:952-944-8000 (DAY)
Emergency Phone Num:800-228-5835X331
Preparer's Name:RYAN MICKELSON
CAGE:56336
=== Contractor Identification ===
Company Name:NOVUS INC
Address:10425 HAMPSHIRE AVE SOUTH
Box:City:MINNEAPOLIS
State:MN
ZIP:55438
Country:US
Phone:952-944-8000 (DAY)
CAGE:56336

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL
CAS:67-63-0
RTECS #:NT8050000
Minumum % Wt:1.
Maxumum % Wt:5.
OSHA PEL:980 MG/M3;400 PPM
ACGIH TLV:983 MG/M3;400 PPM
ACGIH STEL:1230 MG/M3;500 PPM

=====

Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:MAY BE MILDLY IRRITATING TO THE EYES,
NOSE, AND THROAT. MAY CAUSE SKIN IRRITATION TO CERTAIN INDIVIDUALS.
PROLONGED INHALATION OF MIST MAY CAUSE MILD RESPIRATORY IRRITATION.
Effects of Overexposure:RESPIRATORY IRRITATION. HIGH CONCENTRATIONS MAY
CAUSE HEADACHE, DIZZINESS, AND NAUSEA. PROLONGED OR REPEATED
EXPOSURE OR REPEATED EXPOSURE MAY LEAD T
O SKIN IRRITATION AND
DERMATITIS. EYE CONTACT MAY B E IRRITATING AND MAY CAUSE DAMAGE.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH EYES WITH LAGE AMOUNTS OF WATER FOR
AT LEAST 15 MINUTES WHILE HOLDING THE EYELIDS OPEN. GET PROMPT
MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN
THOROUGHLY WITH SOAP AND WATER. GET MEDICAL ATTENTION IF
IRRITATION PERSISTS. INAHALATION: MOVE VICTIM TO FRESH AIR AND
TREAT SYMPTOMATICALLY. SEEK MEDICAL ATTENTION IF IRRITATION
PERSISTS. INGESTION: CONTACT LOC AL POISON CONTROL CENTER OR
PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>93.C, 199.4F
Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING MATERIALS.
Fire Fighting Procedures:NO SPECIAL PROCEDURES REQUIRED.
Unusual Fire/Explosion Hazard:CARBON DIOXIDE AND CARBON MONOXIDE.,
SENSITIVITY TO STATIC DISCHARGE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT. REMOVE
HEAT AN IGNITION SOURCES, VENTILATE AREA, CLEAN UP WITH INERT
ABSORBANT.

===== Handling and Storage =====

Handling and Storage Precautions:COMBUSTIBLE LIQUID. STORE IN CLOSED
CONTAINER IN COOL WELL VENTILATED AREA.
Other Precautions:KEEP FROM FREEZING

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:NOT NORMALLY REQUIRED. FOR SYMPTOMS OF
OVEREXPOSURE, WEAR NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:LOCAL EXHAUST MAY BE NECESSARY UNDER SOME USEAGE/HANDLING
CONDITIONS. SPECIFIC NEEDS SHOULD BE ADDRESSED BY HEALTH/SAFETY
PERSONNEL.

Protective Gloves:CHEMICAL RESISTANT GLOVES ARE RECOMMENDED.

Eye Protection:NOT NORMALLY REQUIRED, HOWEVER THE USE OF SAFETY GLASSES
IS RECOMMENDED

Other Protective Equipment:IF POSSIBLE, EYE WASH AND SA
FETY SHOWER

SHOULD BE AVAILABLE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=36.7C, 98.F

Vapor Pres: