View NSN Online: https://aerobasegroup.com/nsn/8040-00-810-5414

Product ID:TWO PART EPOXY A-1177-B-2 MSDS Date:02/15/1999 FSC:8040 NIIN:00-810-5414 Status Code:A MSDS Number: CLQZG === Responsible Party === Company Name: SIA ADHESIVES INC Address:123 W BARTGES ST **City:AKRON** State:OH ZIP:44311-1081 Country:US Info Phone Num: 330-374-2786 / 330-374-2900 Emergency Phone Num:330-374-2900 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:1HS43 === Contractor Identification === Company Name: SIA ADHESIVES INC Address:123 W BARTGES ST Box:City:AKRON State:OH ZIP:44311-1081 Country:US Phone: 330-374-2786 / 330-374-2900 CAGE:1HS43

Ingred Name:POLYAMIDE SYSTEM CAS:68410-23-1 Code:F = Wt:50.

Ingred Name:CALCIUM CARBONATE CAS:1317-65-3 Code:F RTECS #:EV9580000 = Wt:50. OSHA PE Health Hazards Acute and Chronic:CHRONIC EXPOSURE MAY CAUSE SOME PEOPLE TO DEVELOP SKIN RASH, ALLERGIC REACTION AND/OR SKIN SENSITIZATION.
Effects of Overexposure:SKIN: PROLONGED OR REPEATED EXPOSURE MAY CAUSE MODERATE IRRITATION; MAY CAUSE ALLERGIC REACTION AND SENSITIZATION IN SOME INDIVIDUALS. EYE: MODERATE TO SEVERE IRRITATION.
Medical Cond Aggravated by Exposure:SKIN RASHES.

===

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH AREA WITH PLENTY OF SOAP AND WATER.SEE A PHYSICIAN.EYE: FLUSH WITH WATER FOR 10 MINUTES.SEE A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION.

Flash Point Method:TOC Flash Point:=248.9C, 480.F Extinguishing Media:CARBON DI OXIDE, FOAM, DRY CHEMICAL. Fire Fighting Procedures:DO NOT ENTER CONFINED SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT. INCLUDING NIOSH APPROVED SELF CONAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE KNOWN

Spill Release Procedures: AVOID SKIN AND EYE CONTACT, SCRAPE UP AND PLACE IN CONTAINER.

Handling and Storage Precautions: AVOID PROL

ONGED SKIN AND EYE CONTACT, FOR INDUSTRIAL USE ONLY, KEEP OUT OF THE REACH OF CHILDREN.STORE IN A COOL DRY PLACE, AWAY FROM SOURCES OF HEAT. Other Precautions:IN ADDITION TO ANY LISTED PRECAUTIONS, YOU SHOULD CONSULT YOUR OCCUPATIONAL SAFETY AND HEALTH SPECIALIST TO INSURE THAT SUGGESTED HANDLING PROCEDURES WILL BE ADEQUATE AND IN COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.
======================================
Ventilation:LOCAL EXHAUST MA Y BE NEEDED IF MATERIAL IS HEATED. Protective Gloves:IMPERVIOUS. Eye Protection:CHEMICAL GOGGLES. Other Protective Equipment:CLEAN LONG SLEEVE, LONG LEG CLOTHING. Supplemental Safety and Health
======================================
Vapor Density:HEAVIER Spec Gravity:1.42137 Appearance and Odor:TAN PASTE AMINE ODOR
======================================
Stability Indicator/Materials to Avoid:YES EPOXY RESINS. Stability Condition to A void:AVOID MIXING WITH LARGE AMOUNTS OF EPOXY RESIN. NO MORE THAN TWO POUNDS. Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, AMMONIA, OTHERS POSSIBLE. Conditions to Avoid Polymerization:WILL NOT OCCUR.
======================================
Waste Disposal Methods:THIS MATERIAL IF DISCARDED MAY BE HAZARDOUS AS DEFINED BY GOVERNMENT REGULATIONS AND, THEREFORE MAY BE SUBJECT TO STORAGE, TRANSPORTATION AND DISPOSAL REQUIREMENTS. DISCA RD IN ACCORDANCE WITH LOCAL, S TATE AND FEDERAL REGULATIONS.
======================================

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.