

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY -- EPOXY RESIN COMPOUND  
(PR1829 B-1/2) ACCELERATOR -- 8030-01-369-0049

=====  
Product Identification  
=====

Product ID:EPOXY RESIN COMPOUND (PR1829 B-1/2) ACCELERATOR

MSDS Date:09/24/1996

FSC:8030

NIIN:01-369-0049

Status Code:A

MSDS Number: CLR VX

=== Responsible Party ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Add

ress:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER

CAS:28064-14-4

= Wt:25.

Ingred Name:EPOXY 270

CAS:25068-38-6

RTECS #:CE6880000

= Wt:40.

Ingred Name:NATURAL CALCIUM CARBONATE

CAS:1317-65-3

RTECS #:EV9580000

= Wt:25.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

&lt; Wt:5.

D SILICONES, DI-ME, REACTION PRODUCTS WITH  
SILICA  
CAS:67762-90-7

===== Hazards Identification =====

Effects of Overexposure:EPOXY RESIN EYES: IRRITATING SKIN: IRRITANT.  
MAY CAUSE SKIN SANITIZATION INHALATION:NONE INGESTION: LOW ORDER OF  
ACUTE ORAL TOXICITY EPOXY RESIN EYES: MAY CAUSE SLIGHT  
TRANSIENT (TEMPORARY) EYE IRRITATION SKIN: PROLONGED OR REPEATED  
EXPOSURE MAY  
CAUSE SKIN IRRITATION. MAY RARELY CAUSE AN ALLERGIC SKIN REACTION.  
INHALAT  
ION: AT  
ROOM TEMPERATURE, EXPOSURES TO VAPORS ARE UNLIKELY TO PHYSICAL  
PROPERTIES; HIGHER  
TEMPERATURES MAY GENERATE VAPOR LEVELS SUFFICIENT TO CAUSE IRRITATION.  
INGESTION:SINGLE DOSE ORAL TOXICITY IS LOW. THE ORAL LD50 FOR RAT  
IS >4000 MG/KG CARBON BLACK  
CONTAINS SMAL L AMOUNTS OF TIGHTLY ADSORBED POLYAROMAT

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WARM WATER FOR 15 MINUTES. IF SYMPTOMS  
PERSISTS, CONSULT A PHYSICIAN.  
SKIN:  
WASH WITH SOAP AND WATER. IF SYMPTOMS PERSISTS, CONSULT A  
PHYSICIAN. INHALATION:REMOVE TO FRESH AIR. IF SYMPTOMS ARE PRESENT,  
CONSULT A PHYSICIAN INGESTION: DRINK  
LARGE AMOUNTS OF WATER. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:>93.3C, 200.F  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER.  
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.  
Unusual Fire/Explosion Hazard:NONE KNOWN

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH A  
SUITABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND  
BEFORE SMOKING OR EATING. AVOID INGESTION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE  
Ventilation:GENERAL VENTILATION  
Protective Gloves:PLASTIC O

R RUBBER GLOVES  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:NONE KNOWN  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=260.C, 500.F  
B.P. Text:500-554F  
Vapor Density:N VOLATILE  
Spec Gravity:1.37  
Appearance and Odor:BLACK PASTE  
Percent Volatiles by Volume:0 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG AMINES  
Stability Condition to Avoid:NOT KNO  
WN  
Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE, ALSO  
OXIDES OF SILICON MAY BE EVOLVED.

===== Toxicological Information =====

Toxicological Information:NONE SPECIFIED BY RESPONSIBLE PARTY.

===== Ecological Information =====

Ecological:NONE SPECIFIED BY RESPONSIBLE PARTY.

===== Disposal Considerations =====

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA  
REGULATIONS. CONSULT STATE REGULATIONS  
PRIOR TO DISPOSAL OF SPILLAGE.

===== MSDS Transport Information =====

Transport Information:US DOT PROPER SHIPPING NAME: METHANOL SOLUTION.  
UN IDENTIFICATION NUMBER: UN1230. PACKING GROUP: II. HAZARD CLASS:  
3. US DOT ERG GUIDE NUMBER: 27.

===== Regulatory Information =====

SARA Title III Information:NONE SPECIFIED BY RESPONSIBLE PARTY.  
Federal Regulatory Information:NONE SPECIFIED B

Y RESPONSIBLE PARTY.

State Regulatory Information:NONE SPECIFIED BY RESPONSIBLE PARTY.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.